




## City Element + SQ




T10851 Coin



T10853 Emerald



T10854 Cerulean




T10805 Smokey


### Recommended Installation Method



1/4 Turn



Ashlar



Brick



### Specifications

|                 |                                   |
|-----------------|-----------------------------------|
| Construction    | 1/12" Tufted Multi Loop           |
| Yarn            | 100% nexlon™ Nylon                |
| Pile Weight     | 16 oz/yd <sup>2</sup>             |
| Total Thickness | 7.7mm                             |
| Backing         | Recyclable Commercial Duraback    |
| Tile Size       | 50cm x 50cm                       |
| Packing         | 20 pcs per box (5m <sup>2</sup> ) |

### Performance

|                             |  |
|-----------------------------|--|
| Radiant Panel               | ASTM E 648 Class 1   |
| Smoke Density               | ASTM E662 Less than 450  |
| Static Propensity           | AATCC 134 Less than 3.5KV  |
| Colour Fastness to Light    | AATCC 16E ≥4   |
| Dimension Stability         | AACHEN ≤0.2%   |
| Foot Traffic Recommendation | Heavy Commercial   |
| Antimicrobial               | Health Guard   |
| Certificates                | Singapore Green Label Certification<br>Singapore Green Building Product Certification<br>(4 ticks) |