

ROYAL WELCOME



310 YELLOW

CUT PILE SOLID COLOR

Please note: Images are for illustration use only, there may be a slight color difference between the picture and the actual carpet.



495 ALMOND BEIGE



310 Yellow



442 Khaki



427 RED



427 Red



494 Champagne



457 Oriental Blue



723 Poodle Grey



495 Almond Beige

ROYAL WELCOME Specifications

Construction	1/8" Tufted Cut Pile
Yarn Composition	100% Solution Dyed Heatset Polypropylene
Tufted Pile Weight	Ca. 900 g/m ² (26.5 oz/yd ²) (+/- 10%)
Total Weight	Ca. 1700 g/m ² (50 oz/yd ²) (+/- 10%)
Pile Height	Ca. 8 mm (+/-5%)
Total Height	Ca. 9 mm (+/-5%)
Stitch Rate	33 per 10 cm
Tuft Density	138,600 tufts/m ²
Standard Roll Size	3.66m (+/- 2%) x 30m (+/-2%)

Performance

(as tested by ITTS Inc. USA)

Static Control	Pass - Max. 4 kV (AATCC 134-1996)
Tuft Bind	Pass - 3.1 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 0.1% change (AACHEN)
Flammability	
- Pill Test	Pass - 8 (ASTM-D-2859-96)
- Smoke Density	Pass - Max. 450 (ASTM-E-662-06)
Colourfastness	
- to light	Excellent - 5 (AATCC-16E)
- to wet & dry crocking	Excellent - 4.5 (AATCC-165)
- to Ozone	Excellent - 5 (AATCC-129)

Warranties

10 Year Residential Carpet Wear Warranty
Lifetime Antishock Carpet Warranty

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.



MADE IN DUBAI, U.A.E.

ROYALWELCOME