

ELEVATE YOUR SPACE WITH OUR LUXURIOUS ROYAL MIST, TUFTED CUT PILE AND FRIEZE CARPETS WITH UV TREATED YARN FOR LONG-LASTING BEAUTY.

33 SEA CASTLE










33 Sea Castle



55 Classy Grey



22 Silver Dome



44 Sleek Wood



66 Moss Grey

ROYAL MIST Specifications

1/8" Tufted Cut Pile Friesé 100% Solution Dyed Polyester Construction Yarn Composition Ca. 1200 g/m² (35.3 oz/yd²) (+/- 10%) Ca. 2200 g/m² (64.8 oz/yd²) (+/- 10%) Tufted Pile Weight **Total Weight** Ca. 11 mm (+/- 0.5 mm) Pile Height Total Height Ca. 13 mm (+/- 0.5 mm) Density (APYD) 2942 oz/yd3 Tuft Density 148,050 stitches/m² Stitch Rate 47 per 10 cm **Primary Backing** Woven Secondary Backing Standard Roll Size Action Fleece 3.66m (+/-2%) x 30m (+/-2%) **UV Treated Yarn** Pile Treatment

Performance

Odour Test Hazard Chemical - Antimicrobial

Oragnotin CompoundsHeavy Metals

- Chlorinated Organic Carriers

- Disperse Dye

Disperse Dye

- Carcinogenic Dyes

- Formaldehyde Fastness to Rubbing (Dry) Fastness to Water Fastness to Perspiration Pass (SASO GSO 1957)

Pass (LFGB B82.02-8) Pass (SASO GSO 1957) Pass (SASO GSO 1957) Pass (SASO GSO 1957)

Pass (SASO GSO 1957)
Pass (SASO ISO 16373-1, SASO ISO

16373-2)

Pass (SASO ISO 16373-1, SASO ISO 16373-2, SASO ISO 16373-3)
Pass (SASO ISO 14184-1)

≥ 4 - 5 (EN ISO 105-X12) ≥ 4 - 5 (EN ISO 105-E01) ≥ 4 - 5 (EN ISO 105-E04)

Warranties

10 Year Residential Carpet Wear Warranty Lifetime Antishock Carpet Warranty

Ideal for Bedroom, Living Room, Dining Room, Entrance, Hallway, Study Room, and for Moderate Hospitality Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dye lot variations, actual material may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.









Made In Dubai, U.A.E

ROYALMIST