


# TOP BRASS

CARPET TILES

100% SOLUTION DYED NYLON

## SIMPLICITY IN VISUAL FORM




1470 ECRU BEIGE



“  
**COLOUR  
CO-ORDINATED  
& DESIGN  
COMPATIBLE WITH  
TOP ATTRACTION**

**TOP BRASS | 1430 STYGIAN GREY**  
**TOP ATTRACTION | 1330 STERLING ASH**

In Tile Size: 50 cm x 50 cm



# TOP BRASS

## SWATCHES

In Tile size 50cm x 50cm

*Tile pattern are packed randomly per box.*



**1410 SHADOW PEWTER**



**1430 STYGIAN GREY**



**1440 CHARCOAL EMBER**



**1470 ECRU BEIGE**

Scan QR code to view  
Carpet Tiles Maintenance Guide



*Slight color variation may occur from dye lot to dye lot. Kindly check stock availability with us before confirming the order.*



## TOP BRASS Specifications

Construction	1/12" Multi-Level Loop Pattern
Yarn Composition	100% Solution Dyed Nylon
Tufted Pile Weight	Ca. 678 g/m <sup>2</sup> (20 oz/yd <sup>2</sup> ) (+/- 10%)
Total Weight	Ca. 4000 g/m <sup>2</sup> (112 oz/yd <sup>2</sup> ) (+/- 10%)
Pile Height	Ca. 4 mm (+/- 0.5 mm)
Total Height	Ca. 6 mm (+/- 0.5 mm)
Density (APYD)	4,572 ozs/yd <sup>3</sup>
Tuft Density	143,866 stitches/m <sup>2</sup>
Stitch Rate	51.2 per 10 cm
Backing	EcoAce Polyolefin Backing
Tile Size	50 cm x 50 cm
Packing	20 pcs per box (5 m <sup>2</sup> )

## Performance

(as tested by ITTS Inc. USA)

Stain Resistance	9 (AATCC-175-2003)
Static Control	Pass - Max. 4 kV (AATCC 134-1996)
Tuft Bind	Pass - 6.8 lbs (ASTM-D-1335)
Dimensional Stability	Pass - Max. 2% change (AACHEN)
Indoor Air Quality (V.O.C.)	Pass - No VOC Detected (ASTM-D5116-10)
Impact Sound Insulation	ΔLw: 28 dB (ISO 10140)
Sound Absorption	αw = 0.25 (H) (ISO 354) Hz 125 250 500 1000 2000 4000 αs 0.00 0.05 0.30 0.20 0.20 0.25
Flammability	
- Radiant Panel	Pass - Class I (ASTM-E-648-06)
- Pill Test	Pass - 8 (ASTM-D-2859-96)
Colourfastness	
- to light	Excellent - 5 (AATCC-16E)
- to wet & dry crocking	Excellent - 5 (AATCC-165)
- to ozone	3 (AATCC-129)

## Warranties

15 Year Carpet Wear Warranty  
Lifetime Anti-shock Carpet Warranty  
Ideal for Heavy Commercial Use.

The subfloor should be dry, smooth, flat, dust-free and resistant to compression and load-bearing. The seams may remain visible to the eye and this should be accepted as an inherent characteristic of carpet tiles. Due to dye lot variations, actual colour may vary slightly from the samples. Chair pads are recommended to prevent premature wear of carpet.


## Environment

The design and production of Top Brass Tile conforms to the ISO 14001:2004 Environmental Management System and complies with environmental regulations.

As a responsible manufacturer and to minimize our carbon footprint, a majority of our excess production materials are recycled in-house resulting in a minimum of 10% recycled content in our tile backing. Top Brass Tile does not contain any PVC in its manufactured materials and packaging.

Top Brass Tile is an environmentally friendly green carpet.

## Installation Method



Monolithic Quarter-Turn Ashlar Brick

**Declare.**



**TOPBRASS**  
CARPET TILE