




# TRUE ACE SQ




1621 Beginning-1



1621 Beginning-2




1621 Beginning-3




1621 Beginning-4




1622 Continuation-1




1622 Continuation-2




1622 Continuation-3




1622 Continuation-4




1623 Development-1




1623 Development-2




1623 Development-3




1623 Development-4




1624 Fullfillment-1



1624 Fullfillment-2



1624 Fullfillment-3



1624 Fullfillment-4

## Specifications

<b>Construction</b>	1/10" Multi-Level Loop Pattern
<b>Yarn</b>	100% Solution Dyed Nylon
<b>Pile Weight</b>	28 oz/yd <sup>2</sup>
<b>Pile Thickness</b>	Between 3 to 6mm
<b>Stitch Rate</b>	38 per 10 cm
<b>Secondary Backing</b>	ECO Cushion Backing
<b>Tile Size</b>	50cm x 50cm
<b>Packing</b>	14 pcs per box (3.5m <sup>2</sup> )

## Performance

<b>Flamability tests</b>		
a) Radiant Panel	Pass - Class II	(ASTM E-648-17)
b) Pill Test	Pass 8	(ASTM-D-2859-16)
c) Smoke Density	Pass – Max. 450	(ASTM-E-662-15a)
<b>Stain Resistance</b>	8	(AATCC-175-2003)
<b>Wear Classification</b>	Ideal for Heavy Contract Use	